

AL-A03 WIN Call / charger

Key Specifications/Special Features:

1. Synthesized or Crystal Type
2. Tone / Vibration only pager
3. For guest paging, or nurse paging or church paging
4. PC Programmable
5. Hinged belt clip
6. Charger stand available



AL-A03

AL-A03 Rich Sophistication:

- * Tone, vibrate, and flashed alert
- * Over the air "off "
- * LCD Direct Show Message (option)
- * 71 default and 10 programmable phrases (option)
- * 4 addresses (with four functions per address)
- * Programmable Alert type
- * One LED (Heartbeat, Alert, Out of range, Low battery)
- * One "Push" button to turn pager off
- * Ni-MH Rechargeable battery



Charger

Specifications:

Model	AL-A03
Frequency	138~174MHz, 408~473MHz
Paging Sensitivity	512bps - 5 μ V/M, 1200bps - 7 μ V/M, 2400bps - 9 μ V/M
Bit Rate	512 / 1200 / 2400bps for POCSAG
Channel Spacing	25Khz
Code Format	POCSAG
Spurious Rejection	40db below carrier
Alert Tone Loudness	85db @ 10 cm
Capcodes	4 Capcodes for POCSAG
Dimension	51 (L) x 74 (W) x 28 (H) mm
Weight	Approximately 76 g